```
0021  ## Behaviour changes based on our name

0023  INTERFACE_PARAM = ${lookup {$interface_address} cdb {DB/addrparams.cdb} }
      SENDER_PARAM    = ${lookup {$sender_host_address} cdb {DB/addrparams.cdb} }
0025
      PARAM           = INTERFACE_PARAM
0027
      NAME            = ${extract {name}{PARAM} {$value} {localhost} }
0029
      FULL_HOSTINFO   = $primary_hostname (${if def:interface_address \
0031                          {NAME [$interface_address]:$interface_port} \
                            {NAME} })
```

```
      # ppsw has a generous message size limit, Hermes less so --
0193  # see also the cyrus LMTP limit and the Exim client limit
      message_size_limit      = ${extract {msgsizelim}{PARAM} {$value} {100M} }
```

```
      # The default ACL name is based on the default NAME of localhost.
0213
      acl_smtp_connect        = acl_conn_${extract {acl}{PARAM} {$value} {local} }
0215  acl_smtp_helo           = acl_helo_${extract {acl}{PARAM} {$value} {local} }
      acl_smtp_rcpt           = acl_rcpt_${extract {acl}{PARAM} {$value} {local} }
0217  acl_smtp_data           = acl_data_${extract {acl}{PARAM} {$value} {local} }
```

```
0223  # server-side TLS settings
      tls_advertise_hosts     = ${if exists{CERTS/server/NAME} {*} {} }
0225  tls_certificate         = CERTS/server/NAME
      tls_dhparam             = CERTS/dhparam
0227  tls_on_connect_ports    = 465
```

```
0245  # see also tls_on_connect_ports above
      daemon_smtp_ports       = 25 : 465 : 587
```