```
acl_rcpt_mx:

  # This service is only available on port 25.

  require
    message        = No SMTP service for unauthorized users
    condition      = PORT25

  # Make it easy to get help

  accept
    domains        = +our_domains
    local_parts    = +postmasterish

  # We accept email only for domains that we know about.
  # This check is cheap so we do it early to save time.

  require
    message        = Relaying is not permitted
    domains        = +our_domains

  # Do some anti-spam checking for non-friendly machines.

  deny
  ! hosts          = +relay_hosts
  ! acl            = aux_check_spam

  # Do cheap sender domain verification to avoid further work.

  require
    verify         = sender

  # All recipient addresses must be valid, more or less.

  require
    message        = ${acl_verify_message}\n\
                     See http://www.cam.ac.uk/cs/email/bounce.html
    verify         = recipient/callout=use_sender,defer_ok

  # Do more thorough sender address checks. We do this after verifying the
  # recipient address to reduce the number of sender callouts.

  require
    acl            = aux_verify_sender

  # Don't accept email if we are too busy. We keep this check at the end
  # of the ACLs and ensure we do it only once because it can be expensive.

  defer
    message        = Sorry, too busy. Try again later.
    condition      = ${if or{{ eq{$ACL_BUSY}{yes} } \
                             { <{300}{${run {/opt/exim/sbin/exim_incount} }} }} }
    set ACL_BUSY   = yes

  # Every check has been passed.

  accept
```