```
0249  smtp_banner             = \
              FULL_HOSTINFO ESMTP Exim $version_number+ppsw+$compile_number $tod_full\
0251          ${if match{PARAM}{acl=mx} {${run {/usr/bin/fortune -s} {\n$value} }} }
```

```
      acl_conn_mx:
0511
        # Be nice to friendly machines.
0513
        accept
0515      hosts          = +relay_hosts

0517    # Assume we won't have to delay.

0519    warn
          set ACL_DELAY  = 0s
0521
        # We delay if the sender is blacklisted.
0523
        warn
0525      dnslists       = list.dsbl.org : \
                           multihop.dsbl.org : \
0527                       rbl-plus.mail-abuse.ja.net : \
                           combined.njabl.org : \
0529                       relays.ordb.org : \
                           dnsbl.sorbs.net : \
0531                       sbl-xbl.spamhaus.org
          set ACL_DELAY  = 5s
0533
        # We delay if the sender has bad DNS.
0535
        warn
0537    ! verify         = reverse_host_lookup
          set ACL_DELAY  = 5s
0539
        # Do whatever delay we worked out.
0541
        accept
0543      delay          = $ACL_DELAY
```

```
0547  acl_helo_mx:

0549    # Be nice to friendly machines.

0551    accept
          hosts          = +relay_hosts
0553
        # We delay if the sender says the wrong hello domain.
0555
        warn
0557    ! verify         = helo
          set ACL_DELAY  = 5s
0559
        # Do whatever delay we worked out.
0561
        accept
0563      delay          = $ACL_DELAY
```